



Ceiling-mounted monobloc units



GENERAL DESCRIPTION

Pre-charged units

Equipped with hermetic reciprocating compressor and refrigerant charge R455A (A2L – GWP 148)

Wide application range

Developed to work at wide external temperatures range (min temp +10°C , max temp +43°C). Equipped with condenser fan/s pressure switch (fixed set). Set point from +5°C to -5°C for MT units and set point from -18°C to -25°C for LT units.

Easy installation

Installation through a hole on the roof of the cold room.

Equipped with the drain heater and the pipe to remove condensate water.

“Plug and play” solution

Equipped with the electronic card and the remote keyboard, a pre-arranged door switch cable, a pre-arranged room light cable, a pre-arranged door heater cable (for LT units only)



TECHNICAL DATA

Model: CMN034

GENERAL DATA		
Compressor power	cc	18,30
Compressor type		Hermetic
Refrigerant charge		R455A
Defrost system		Hot gas

ELECTRICAL DATA		
Voltage	V/ph/Hz	230/1/50
Max power input	W	1092
Max operating current	A	5,50

CONDENSER		
Fan	n. x Ø	1 x 254mm
Air flow rate	m³/h	800
EVAPORATOR		
Fan	n. x Ø	1 x 200mm
Air flow rate	m³/h	410
Air thrown	m	5

WEIGHT and DIMENSIONS		
Dimensions	Ref.	Fig. 1
Net Weight	kg	56
Gross Weight	kg	72
Packing		Wooden crate



Cooling capacity

Ext. Temp.	Room Temp.		*
25°C	+5 °C	W	1410
		m³	13,0
	0 °C	W	1280
		m³	12,2
	-5 °C	W	1013
		m³	7,1
32 °C	+5 °C	W	1320
		m³	10,7
	0 °C	W	1190
		m³	8,3
	-5 °C	W	952
		m³	6,7
43 °C	+5 °C	W	1130
		m³	7,4
	0 °C	W	1049
		m³	6,1
	-5 °C	W	765
		m³	4,4


*Suggested m3 Volume for cold rooms with 80mm wall thickness and insulated floor



Installation



Shipment information



Additional Options

- Crankcase heater (up to -10°C ext.temp)
- Water-cooled condenser (with pressure valve)
- WI-FI connection to a remote monitoring system
- Cataphoresis protection on condenser and evaporator coils
- Special voltage (please contact our Engineering department)
- RS485 serial interface