



Wall-mounted monobloc units with propane



General description

Pre-charged units

Equipped with hermetic reciprocating compressor working with R290 "green" refrigerant (propane – GWP 3). Each circuit includes less than 150 gr of propane.

Wide application range

Developed to work at wide external temperatures range (min temp +10°C , max temp +43°C). The unit includes a condenser fan pressure switch. Set point from +5°C to -5°C for MT units and set point from -18°C to -25°C for LT units.

Easy installation

Straddle mounted installation, additional option with panel kit to be installed through the wall. Equipped with the drain heater and automatic system to remove condensate water)

"Plug and play" solution

Equipped with the electronic controller, a pre-arranged door switch cable, a pre-arranged room light cable, a pre-arranged door heater cable (for LT units only)



TECHNICAL DATA

Model: NXK127

GENERAL DATA		
Compressor		27,80 cc
Compressor type		Hermetic
Refrigerant charge		R290
Defrost system		Hot gas

ELECTRICAL DATA		
Voltage	V/ph/Hz	230/1/50
Max power input	W	1196
Max operating current	A	6,18

CONDENSER		
Fan	n. x Ø	1 x 254mm
Air flow rate	m ³ /h	800
EVAPORATOR		
Fan	n. x Ø	1 x 254mm
Air flow rate	m ³ /h	630
Air thrown	m	6

WEIGHT and DIMENSIONS		
Dimensions	Ref.	Fig. 1
Net Weight	kg	55
Gross Weight	kg	85
Packing		Wooden crate

Cooling capacity


Ext. Temp.	Room Temp.		*
25 °C	-18 °C	W	1172
		m ³	11,8
	-20 °C	W	1107
		m ³	11,6
	-25 °C	W	947
		m ³	7,1
32 °C	-18 °C	W	1095
		m ³	8,6
	-20 °C	W	1031
		m ³	8,3
	-25 °C	W	874
		m ³	5,8
43 °C	-18 °C	W	958
		m ³	6,3
	-20 °C	W	902
		m ³	6,0
			759
			4,0




sicaf

; with 100mm wall thickness and insulated floor

Installation




Versione accavallata




340
Ø22 mm

Versione a tampone (optional)



Shipment information



Additional Options

- Panel kit (through the wall installation)
- Cataphoresis protection on evaporator coil
- Special voltage (please contact our Engineering department)
- RS485 serial interface