


NEK6210U



ENGINEERING CODE
862CA41



REFRIGERANT
R-290



POWER SUPPLY
220-240 V 50 Hz



APPLICATION
MBP



MOTOR TYPE
CSIR



STANDARD
EN12900



COOLING CAPACITY
606 W



EFFICIENCY
1.76 W/W



DATA

GENERAL DATA

Model	NEK6210U
Type	Hermetic Reciprocating
Technology	ON/OFF
Compressor Application	MBP
Expansion Device	Capillary Tube or Expansion Valve
Compressor Cooling	Fan/220
HP	1/3
Starting Torque	HST
Plant	SLOVAKIA

ELECTRICAL DATA

Start Winding Resistance	31.7 Ω at 25°C
Run Winding Resistance	5.18 Ω at 25°C
Locked Rotor Amperage (LRA) 50Hz	16.1 A

MECHANICAL DATA

Displacement	8.77 cm³
Oil Charge	350 ml
Oil Type	AB
Oil Viscosity	ISO32
Weight	10.5 Kg

ELECTRICAL COMPONENTS

Start Capacitor	53-64 µf/330 V
CSR CSIR BOX	No
Starting Device Type	RELAY
Starting Device Description	MTRP-0029*
Overload Protection	T0964/G6

PERFORMANCE

TESTED CONDITIONS

Tested Refrigerant	R-290
Tested Application	MBP
Tested Standard	EN12900
Tested Cooling	Fan
Tested Voltage	220 V
Refrigerant Temperature	Dew

RATED POINTS

Condensing Temperature °C	Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
45	-10	606	1.76	344	2.41	7.46

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data generated in accordance to EN 12900:2013 polynomial equation and tolerance guidelines.

PERFORMANCE CURVE


Condensing Temperature 35°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-20	463	1.71	270	2.18	5.13
-15	570	1.96	290	2.25	6.35
-10	698	2.26	309	2.31	7.82
-5	850	2.61	326	2.35	9.57
0	1027	3.05	336	2.39	11.66
5	1232	3.64	338	2.42	14.11
10	1467	4.46	329	2.44	16.97

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data generated in accordance to EN 12900:2013 polynomial equation and tolerance guidelines.

PERFORMANCE CURVE				Condensing Temperature 45°C	
Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-20	400	1.35	297	2.24	4.86
-15	494	1.55	319	2.33	6.04
-10	606	1.76	344	2.41	7.46
-5	739	2.00	369	2.48	9.15
0	894	2.28	391	2.55	11.16
5	1072	2.63	408	2.60	13.53
10	1277	3.07	416	2.66	16.29
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data generated in accordance to EN 12900:2013 polynomial equation and tolerance guidelines.					

PERFORMANCE CURVE				Condensing Temperature 55°C	
Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-10	506	1.39	365	2.52	6.95
-5	620	1.57	396	2.63	8.59
0	753	1.76	427	2.73	10.52
5	906	1.99	455	2.82	12.80
10	1082	2.26	478	2.91	15.46
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data generated in accordance to EN 12900:2013 polynomial equation and tolerance guidelines.					




External


EXTERNAL CHARACTERISTICS			
Base Plate		SMALL	
Tray Holder		NO	
Connector	Internal Diameter	Shape	Material
Suction	8.1 mm	SLANTED 42°	COPPER
Discharge	6.1 mm	STRAIGHT	COPPER

EXTERNAL DIMENSIONS

SHELL



BASE



FENCE

