


NEK6213GK



ENGINEERING CODE
959BA51



REFRIGERANT
R-404A



POWER SUPPLY
220-240 V 50 Hz



APPLICATION
MBP



MOTOR TYPE
CSIR



STANDARD
EN12900



COOLING CAPACITY
954 W



EFFICIENCY
1.43 W/W

DATA

GENERAL DATA

Model	NEK6213GK
Type	Hermetic Reciprocating
Technology	ON/OFF
Compressor Application	MBP
Expansion Device	Capillary Tube or Expansion Valve
Compressor Cooling	Fan/220
HP	1/2+
Starting Torque	HST
Plant	SLOVAKIA

ELECTRICAL DATA

Start Winding Resistance	20.88 Ω at 25°C
Run Winding Resistance	3.93 Ω at 25°C

MECHANICAL DATA

Displacement	12.11 cm ³
Oil Charge	350 ml
Oil Type	ESTER
Oil Viscosity	ISO22
Weight	11.6 Kg

ELECTRICAL COMPONENTS

Start Capacitor	53-64 µf/330 V
CSR CSIR BOX	No
Starting Device Type	RELAY
Starting Device Description	MTRP-0050*
Overload Protection	T0743/G6

PERFORMANCE

TESTED CONDITIONS

Tested Refrigerant	R-404A
Tested Application	MBP
Tested Standard	EN12900
Tested Cooling	Fan
Tested Voltage	220 V
Refrigerant Temperature	Dew

RATED POINTS

Condensing Temperature °C	Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
45	-10	954	1.43	666	-	28.64

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

PERFORMANCE CURVE

Condensing Temperature 35°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-20	818	1.58	517	-	21.17
-15	984	1.75	562	-	25.78
-10	1171	1.91	613	-	30.91
-5	1387	2.08	666	-	36.91
0	1638	2.29	715	-	44.11
5	1930	2.55	756	-	52.82
10	2271	2.90	784	-	63.39

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

PERFORMANCE CURVE


Condensing Temperature 45°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-20	645	1.16	558	-	19.00
-15	790	1.31	605	-	23.52
-10	954	1.43	666	-	28.64
-5	1143	1.55	735	-	34.69
0	1363	1.69	807	-	42.01
5	1622	1.85	876	-	50.92
10	1926	2.05	938	-	61.76
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

PERFORMANCE CURVE

Condensing Temperature 55°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-10	749	1.10	683	-	26.53
-5	905	1.19	760	-	32.56
0	1089	1.29	845	-	39.91
5	1309	1.40	935	-	48.93
10	1571	1.53	1025	-	59.95
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					




External


EXTERNAL CHARACTERISTICS			
Base Plate		SMALL	
Tray Holder		NO	
Connector	Internal Diameter	Shape	Material
Suction	8.1 mm	SLANTED 42°	COPPER
Discharge	6.1 mm	STRAIGHT	COPPER

EXTERNAL DIMENSIONS

SHELL



BASE



FENCE

