



Model: AJ2432P-FZ3A

(AJ2432P-FZ)

Product Description

Compressor Type: Reciprocating

Application: LBP - Low Back Pressure

Refrigerant: R-404A/R-452A/R-454C/R-455A

Voltage/Frequency: 220-240V ~ 50Hz

Version: AJ2 Series

Specifications

General

- Evaporating Temp. Range : -40°C to -10°C (-40°F to 14°F)
- Motor Torque: High Start Torque (HST)
- Compressor Cooling: Fan

Mechanical

- Displacement (cc): 18.3
- Oil Type: Polyolester
- Viscosity (cSt): 32
- Oil Charge (cc): 475

Electrical

- Locked Rotor Amps (LRA): 20.8
- Rated Load Amps (RLA 60Hz): 0
- Voltage Range (50Hz): 198-253
- Rated Load Amps (RLA 50Hz): 2.5
- Max. Continuous Current (MCC in Amps): 5.7
- Motor Resistance (Ohm) - Main: 4.5
- Motor Resistance (Ohm) - Start: 9.8
- Motor Type: CSR

Agency Approval

VDE_LISTED, CE_LISTED, CCC_LISTED, GOST_LISTED

Performance

[See all performance data](#)

Item

AJ2PB1JF602A06

AJ2PB1JF602A06-M

AJ2PB1JF703A06

AJ2PB1JF703A06-M

AJ2PB1JF703A08

AJ2PB1JF703A08-M

AJ2PB1JF703A66