



Model: AJ4513P-FZ3A

(AJ4513P-FZ)

Product Description

Compressor Type: Reciprocating

Application: HBP - High Back Pressure

Refrigerant: R-404A/R-448A/R-449A/R-452A/R-454C/R-455A

Voltage/Frequency: 220-240V ~ 50Hz

Version: AJ2 Series

Specifications

General

- Evaporating Temp. Range :-15°C to 15°C (5°F to 59°F)
- Motor Torque: High Start Torque (HST)
- Compressor Cooling: Fan

Mechanical

- Displacement (cc): 24.2
- Oil Type: Polyolester
- Viscosity (cSt): 32
- Oil Charge (cc): 475

Electrical

- Locked Rotor Amps (LRA): 33
- Rated Load Amps (RLA 60Hz): 0
- Voltage Range (50Hz): 198-253
- Rated Load Amps (RLA 50Hz): 6.8
- Max. Continuous Current (MCC in Amps): 11.5
- Motor Resistance (Ohm) - Main: 2.67
- Motor Resistance (Ohm) - Start: 7.89
- Motor Type: CSR

Agency Approval

VDE_LISTED, CE_LISTED, CCC_LISTED, GOST_LISTED

Performance

[See all performance data](#)

Item

- AJ4PK1JF603A04-M
- AJ4PK1JF603A06
- AJ4PK1JF603A06-M
- AJ4PK1JF704A06
- AJ4PK1JF704A06-M
- AJ4PK1JF704A08
- AJ4PK1JF704A08-M
- AJ4PK1JF704A09-M
- AJ4PK1JF704A66
- AJ4PK1JF724A06